

### Nominal Weights and Sizes for #12 AWG SO Multi-conductor Cable

Conductor Quantity	Outside Dim. inches	Weight Per Foot/Lbs.	Recommended Box Mount Grip	Recommended Offset Eye Grip
3	0.610	0.235	B-508	S-508
5	0.730	0.350	B-508	S-508
6	0.790	0.455	B-512	S-512
7	0.795	0.465	B-512	S-512
8	0.850	0.490	B-512	S-512
9	0.910	0.530	B-512	S-512
10	1.020	0.600	B-515	S-515
12	1.045	0.690	B-515	S-515
14	1.110	0.845	B-515	S-515
16	1.165	0.935	B-515	S-515
20	1.300	1.050	B-516	S-516
24	1.455	1.370	B-516	S-516
26	1.490	1.420	B-516	S-516
30	1.520	1.590	B-517	S-517
36	1.625	1.765	B-517	S-517
40	1.660	1.995	B-517	S-517
44	1.865	2.270	B-518	S-518
50	1.975	2.505	B-518	S-518

### Nominal Weights and Sizes for #10 AWG SO Multi-conductor Cable

Conductor Quantity	Outside Dim. inches	Weight Per Foot/Lbs.	Recommended Box Mount Grip	Recommended Offset Eye Grip
3	0.670	0.245	B-508	S-508
5	0.810	0.430	B-512	S-512
6	0.860	0.495	B-512	S-512
7	0.860	0.620	B-512	S-512
8	0.960	0.700	B-512	S-512
10	1.120	0.800	B-515	S-515
12	1.160	0.920	B-515	S-515
16	1.320	1.200	B-516	S-516
20	1.450	1.445	B-516	S-516
24	1.585	1.745	B-517	S-517
26	1.595	1.845	B-517	S-517
30	1.865	2.235	B-518	S-518